



- NOTES:
- 1) MATERIAL: 7075-T6 (OR T651/T6510/T6511/T62) ALUMINUM BAR
PER AMS-QQ-A-225/9 (OR AMS 4122/4123/4186/4187) OR
PER AMS-QQ-A-200/11 (REF DART SPEC M7075T6B)
 - 2) FINISH: HARD ANODIZE IAW MIL-A-8625 TYPE III, CLASS 2, COLOR BLACK,
PRIME IAW MIL-P-23377J TYPE I CLASS N; 1-2 MIL MAX, AS PER QSI 005.
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D4974-1", AGUSTA WESTLAND P/N "TBD", REVISION, BATCH NUMBER AND DATE OF MANUFACTURE,
USING AN X-TENSION STAMP, PER QSI 044 METHOD 6.2
 - 7) WEIGHT: 0.91 lbs (0.42 kgs)
 - 8) UNDIMENSIONED FEATURES CONTROLLED BY CAD MODEL FILE: D4974-1-a.IGES

PRELIMINARY ISSUE

A		NEW ISSUE		DC	13.11.11
REV.		DESCRIPTION		BY	DATE
DESIGN		DC		DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN		DC			
CHECKED		RF		DRAWING NO.	REV. A4
MFG. APPR.		JLM		D4974	SHEET 1 OF 1
APPROVED				TITLE	SCALE
DE APPR.				UPPER RAIL	NTS
DATE		13.11.11		COPYRIGHT © 2013 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	